

TECHNICAL DATA

TAMPER

BT 60, BT 65



Maximum reliability and longevity
All around engine protection




More transparency
Hour counter/tachometer with a service indicator which can be reset



Simple operation
Engine and fuel supply with combined switch

Shipping dimensions in m3

| | |
|--------------|-------|
| BT 60 | 0,262 |
| BT 65 | 0,262 |



Standard Equipment

- Engine Protection System
 - Protective engine covering
 - Paper air filter system with two stages
 - Automatic oil level control
 - Dual fuel filter system
- Vibration insulated steering handle
- Self-cleaning air filter housing
- Protective covering
- Single point lifting device
- Recoil starter
- Plastic castor as loading aid
- Infinitely variable frequency
- Combination of engine stop/fuel switch
- h-/ rpm meter
- 3-2-1 Warranty

Dimensions in mm

| | B | H | L | L1 | W |
|--------------|-----|------|-----|-----|-----|
| BT 60 | 350 | 1030 | 728 | 335 | 230 |
| BT 65 | 350 | 1030 | 728 | 335 | 280 |

Optional Equipment

- Transport device with puncture proof wheels
- Tamper foot widths (160-330mm)
- Tamper foot extensions
- Special painting
- Tool kit
- Service Kit
- Operator protection contact breaker switch
- TOUGH WARRANTY

Technical Data

Weights

| | | |
|-----------------------------|----|----|
| Operating weight CECE | kg | 58 |
| Basic weight | kg | 57 |

Dimensions

| | | | |
|------------------------------------|----|-----|-----|
| Working width (tamper plate) | mm | 230 | 280 |
|------------------------------------|----|-----|-----|

Driving Characteristics

| | | | |
|-------------------------|-------------------|-----|-----|
| Working speed max. | m/min | 20 | 20 |
| Area coverage max. | m ² /h | 276 | 336 |

Drive

| | | | |
|--|-----------------|-----------------|-----|
| Engine manufacturer | Honda | Honda | |
| Type | GXR 120 | GXR 120 | |
| Emission stage | StageV/CARB P.3 | StageV/CARB P.3 | |
| Cooling | air | air | |
| Number of cylinders | 1 | 1 | |
| Performance SAE J 1349 | 2,8 | 2,8 | |
| Fuel | Gasoline | Gasoline | |
| Drive system | mech. | mech. | |
| Fuel comsump. aver. during operation | l/h | 0,9 | 0,9 |

Exciter system

| | | | |
|----------------------|----|----------|----------|
| Frequency | Hz | 10- 11,8 | 10- 11,8 |
| Impact force | kN | 15,0 | 17,0 |
| Jumping height | mm | 70,0 | 70,0 |

Capacities

| | | | |
|------------|---|-----|-----|
| Fuel | l | 3,0 | 3,0 |
|------------|---|-----|-----|

Technical modifications reserved. Machines may be shown with options.

