



## Latitude 6' Web SRL-P

\*See chart for part numbers, hook configurations, and product weights

### FEATURES :

- Quick-locking unit designed for use at low heights.
- 360/180° attachment point offers full range of motion.
- Durable housing increases strength and longevity.
- External shock pack with energy absorber and protective label cover.
- High-strength, lightweight webbing.
- Single leg and dual leg options available.
- Available with various hook options, see chart.
- All components are Z359.12 compliant.



Class  
**1**  
Anchor at or above dorsal D-ring

Product shown:  
019-5045

USER WEIGHT CAPACITY	
ANSI	130-310 lbs. (59-140.6 kg)
OSHA	Up to 420 lbs. (190.5 kg)

STANDARD COMPLIANT WITH	
ANSI	Z359.14-2021
OSHA	1910.140, 1910.66

ANSI CLASS 1 (ABOVE D-RING)	
Max. arrest force	≤ 1,800 lbs. (816.5 kg)
Avg. arrest force	≤ 1,350 lbs. (612.4 kg)
Max. arrest distance	≤ 42 in. (107 cm)
Actual arrest distance	≤ 23 in (58 cm)
Max. free fall distance	24 in. (61 cm)
Use below d-ring	not permitted
Min. required fall clearance	5 ft. 5 in. (1.7 m)
For full clearance requirements, see user instructions	

OSHA (BELOW D-RING)	
Max. arrest force	≤ 1,800 lbs. (816.5 kg)
Avg. arrest force	≤ 900 lbs. (408.2 kg)
Max. arrest distance	N/A
Actual arrest distance	≤ 29 in. (74 cm)
Max. free fall distance	60 in. (152 cm)
Use below d-ring	5 ft. (1.5 m)
Min. required fall clearance	10 ft. 11 in. (3.3 m)
For full clearance requirements, see user instructions	

MATERIAL SPECIFICATION	
Webbing	20 mm UHMPE webbing
Housing	Nylon
Bracket	Steel, aluminum (dependent on configuration)
Hook options	Steel, aluminum, dielectric (dependent on configuration)
Shock pack	Polyester

