



Latitude HD 10' Cable SRL-P

*See chart for part numbers, hook configurations, and product weights

FEATURES :

- Durable housing increases strength and longevity.
- Rugged cable provides extreme durability.
- 360/180° attachment point offers full range of motion.
- Single leg and dual leg options available.
- Available with various hook options, see chart.
- All components are Z359.12 compliant.



Class
1
Anchor at or above dorsal D-ring

Product shown:
SW8008-10

USER WEIGHT CAPACITY	
ANSI	130-310 lbs. (59-140.6 kg)
OSHA	Up to 420 lbs. (190.5 kg)

STANDARD COMPLIANT WITH	
ANSI	Z359.14-2021
OSHA	1910.140, 1910.66

ANSI CLASS 1, OSHA up to 420 lbs. (ABOVE D-RING)	
Max. arrest force	≤ 1,800 lbs. (816.5 kg)
Avg. arrest force	≤ 1,350 lbs. (612.4 kg)
Max. arrest distance	≤ 42 in. (107 cm)
Actual arrest distance	≤ 14 in. (36 cm)
Max. free fall distance	24 in. (61 cm)
Use below d-ring	not permitted
Min. required fall clearance	4 ft. 8 in. (1.4 m)

OSHA 130-310 lbs. (BELOW D-RING)	
Max. arrest force	≤ 1,800 lbs. (816.5 kg)
Avg. arrest force	≤ 900 lbs. (408.2 kg)
Max. arrest distance	N/A
Actual arrest distance	≤ 26 in (66 cm)
Max. free fall distance	24 in. (61 cm)
Use below d-ring	2 ft. (61 cm)
Min. required fall clearance	7 ft. 8 in. (2.3 m)

MATERIAL SPECIFICATION	
Cable	4.8 mm galvanized steel cable
Housing	Polymer
Bracket	Steel, aluminum (dependent on configuration)
Hook options	Steel, aluminum, dielectric (dependent on configuration)
Shock pack	Polyester

