



FS700-25 Through FS700-400

PRO Vertical Lifeline

FEATURES :

- 5/8" Polyester rope
- 1 Snap hook
- Rope tensile strength: 7,500 lbs.
- Hook gate rating: 3,600 lbs.
- Hook minimum breaking strength: 5,000 lbs.
- To be a compliant ANSI Z359.15 system, lifeline must be used in conjunction with a compatible and approved fall arrester with energy absorbing lanyard. See user manual for additional restrictions and specifications.

FALL ARREST POINT(S) :

- 1 Snap hook

ITEM WEIGHT :

- Weight varies by length



USER WEIGHT CAPACITY	
ANSI	130-310 lbs. (59-140.6 kg)
OSHA	Up to 420 lbs. (190.5 kg)

STANDARD COMPLIANT WITH	
ANSI	Z359.15-2014*
OSHA	1926.502, 1910.66, 1910.140

Size(s)		
FS700-25	25 Feet (8 m)	3 lbs. (1 kg)
FS700-50	50 Feet (15 m)	6 lbs. (3 kg)
FS700-75	75 Feet (23 m)	9 lbs. (4 kg)
FS700-100	100 Feet (31 m)	11 lbs. (5 kg)
FS700-150	150 Feet (41 m)	16 lbs. (7 kg)
FS700-200	200 Feet (61 m)	21 lbs. (10 kg)
FS700-250	250 Feet (76 m)	26 lbs. (12 kg)
FS700-300	300 Feet (91 m)	31 lbs. (14 kg)
FS700-400	400 Feet (122 m)	41lbs. (19 kg)

COMPONENT	MATERIAL SPECIFICATION
Snap hook	Zinc plated alloy steel
Rope	Polyester