

# 6' Steel Rolling Scaffold

**Easy one-person assembly**

No tools required for quick setup and tear down



SRS-72 - 6' Steel Rolling Scaffold

LOAD CAPACITY  
**1000 lbs.**

Includes User and Materials

**WERNER®**



Sections stack easily



Protected locking pins prevent accidental release



Deck pin secures plywood to frame



Swivel locking casters



[www.wernerco.com](http://www.wernerco.com)



# 6' Steel Rolling Scaffold

- 1000 lbs. distributed load capacity
- Easy one-person assembly
- No tools required for quick setup and tear down
- Stackable frames (2 high maximum)
- All ball bearing casters remove easily for stacking

- Simple platform adjustment
- Platform height can be adjusted in 2" increments for unique working heights and uneven surfaces
- Compatible and interchangeable with leading competitor



## SPECIFICATIONS SRS-72

Model No.	Description	Approx. Width	Approx. Length	Approx. Height	Approx. Shipping Weight
SRS-72	Steel Rolling Scaffold	29-1/2"	73-3/4"	74-7/8"	127 lbs.

### Includes:

Qty.	Description	Approx. Width	Approx. Length	Approx. Height
2	End Frames	29"	68-3/4"	1-1/2"
2	Side Braces	1-1/2"	73-7/8"	17-7/8"
1	Plywood Deck	28-1/2"	66-3/4"	2"
4	Locking Casters	5-1/8"	1-1/8"	9-7/8"

## ACCESSORIES (available separately)

Model No.	Description	Approx. Width (ea.)	Approx. Length (ea.)	Approx. Height (ea.)	Approx. Shipping Weight (carton)
SRO-72-4	Outrigger (4-pc master carton)	18"	20-3/4"	---	37.5 lbs.
SRG-72	Guard Rail & Toeboard System	28-7/8"	69-5/8"	42"	70.5 lbs.
SRC-72-4	5" Casters (4-pc master carton)	5-1/8"	1-1/8"	9-7/8"	20.0 lbs.
SRD-72	Plywood Deck	28-1/2"	66-3/4"	2"	32.5 lbs.

Note: Guard rail and outriggers required when stacking two units regardless of height.

**SRS-72 - 6' Steel Rolling Scaffold**

**1000** LOAD CAPACITY **lbs.**

*Includes User and Materials*